300Mbps Enhanced Wireless N Router

Model: MW325R


// Highlights

- Maximum Coverage Four 5dBi antennas provide up to 500m² of wireless coverage
- Enhanced Signal High gain antennas dramatically increase the strength and stability of the wireless signal
- 300Mbps Wireless Speed Ideal for HD streaming, online gaming, and large file downloads
- Easy Installation Intuitive webpage guides you through the setup process in minutes





Applications





// Features



Speed

Fast Wireless Speed - Wireless speed up to 300Mbps



Range

Four Omni Directional Antennas – Four fixed antennas provide maximum wireless coverage Enhanced Signal – High quality antennas are arranged to boost wireless performance



Easy Setup

Quick 3-Step Installation – Intuitive webpage supports quick, hassle free installation



Security

Guest Network – Creates two separate networks for you and your guests to ensure safety Parental Controls – Parents can establish appropriate access policies to protect children



Connections



WAN Port: Connect to LAN Ports:

Internet

Connect to desktops, game consoles, and more



// Maximum Wi-Fi Coverage

The MW325R provides wider coverage and more stable wireless performance by precisely arranging four 5dBi antennas that feature advanced antenna technology. You can enjoy smooth streaming, gaming, and browsing from any room in your home.





Specifications

Physical Specifications

Ethernet Ports

3 x 10/100Mbps LAN Ports 1 x 10/100Mbps WAN Port

Button

Reset Button

External Power Supply

5V/0.6A

Dimensions (W x D x H)

167 x 118 x 33mm

Antenna

4 * 5dBi

Package Contents

300Mbps Enhanced Wireless N Router MW325R

Power Adapter

Quick Installation Guide

RJ45 Ethernet Cable

Wireless Specifications

Wireless Standards

IEEE 802.11b/g/n

Frequency

2.4-2.5GHz

Signal Rate

- 11n: Up to 300Mbps (Dynamic)
- 11g: Up to 54Mbps (Dynamic)
- 11b: Up to 11Mbps (Dynamic)

EIRP

<20dBm (EIRP)

Reception Sensitivity

- 270M: -70dBm@10% PER
- 130M: -72dBm@10% PER 6 M: -92dBm@10% PER
- 5 4M: -74dBm@10% PER
- 1 M: -94dBm@10% PER

• 11M: -87dBm@10% PER

Wireless Function

Enable/Disable Wireless Radio, WDS Bridge

Wireless Security

WPA-PSK / WPA2-PSK

Operation Specifications

WAN Type

Dynamic IP/Static IP/PPPoE/L2TP/PPTP

DHCP

Server, DHCP Client List

Port Forwarding

Virtual Server, UPnP, DMZ

Management

Access Control Local Management Remote Management

Firewall Security

IP and MAC Address Binding

Guest Network

2.4GHz Guest Network

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Operating Humidity: 10%~90% Non-Condensing
- Storage Humidity: 5%~90% Non-Condensing

Specifications are subject to change without notice. MERCUSYS is a registered trademark of MERCUSYS TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2017 MERCUSYS TECHNOLOGIES CO., LTD. All rights reserved.