

ADSL2/2+

Single Ethernet Port | USB Device

CT-5611T Combo Router



The CT-5611T ADSL2/2+ Combo Router is equipped with one 10/100 Ethernet port and one USB interface for flexible connectivity in a compact high performance package. It offers WAN access speeds of up to 24 Mbps (ADSL2+) and has full routing capabilities to segment/route IP protocol under an advanced security umbrella.

FEATURES

Fast Connections

The ADSL2/2+ port carries WAN traffic at speeds of up to 24 Mbps (ADSL2+), while Ethernet and USB ports support LAN traffic at speeds up to 100 Mbps. The TR-068 compliant rear panel and LED indicators simplify setup and improve ease-of-use.

Secure Connections

As the first level of protection, a Stateful Firewall (with DoS protection) and NAT/PAT help to isolate the LAN from external threats. Second, IP and MAC address filtering provide fine-grained access control to or from the network. Third, advanced security technologies, such as Virtual Private Networks (VPN) with PPTP/L2TP/IPSec pass-through ensure secure networking.

Flexible Management Toolkit

Supported management tools include SNMP, TELNET, SSH, and a web browser based graphical user interface. These tools provide configuration and control functions including firmware upgrades (via FTP, TFTP, or HTTP) and configuration backup & restoration. The web browser based user interface features auto-PVC configuration, a diagnostic dashboard and other advanced management capability.

Remote Auto-Configuration (TR-069)

TR-069/TR-098/TR-111 standards compatibility ensures interoperability with central office remote management equipment. From the user perspective this reduces downtime and frustration. For the service provider it means improved customer relations and cost savings.

Reliability and Quality

For over 20 years, Comtrend has delivered superior quality products to our customers worldwide. Every product goes through rigorous testing and is backed by a 2 year warranty.

CT-5611T

Single Ethernet Port | USB Device



SPECIFICATIONS

Hardware

- · RJ-11 X1 for ADSL
- · RJ-45 X 1 for LAN
- · USB X 1 for LAN
- · Reset Button X 1
- · Power switch X 1

WAN

- Complies with ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2
- · G.992.5 (ADSL2+):
- Downstream: 24 Mbps Upstream: 1.3 Mbps
- · G.992.3 (ADSL2)
- Downstream: 12 Mbps Upstream: 1.3 Mbps
- · G.DMT
- Downstream: 8Mbps Upstream: 832kbps
- · AnnexM

LAN

- · IEEE 802.3, IEEE 802.3u
- · 10/100 BaseT auto-sense
- · Support MDI/MDX

ATM Attributes

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA); Annex M
- · Support 8 PVCs
- · AAL5
- · UBR/CBR/VBR
- · UNI 3.1/4.0
- · OAM F4/F5

Management

- · SNMP, Telnet, Web-based management
- Configuration backup and restoration
- Software upgrade via HTTP, TFTP server, or FTP server
- · Supports TR-069/TR-098/TR-111 for Remote Management

QoS

· L3 policy-based QoS, IP QoS, ToS

Networking Protocols

- RFC2684 VC-MUX, LLC/SNAP encapsulations for bridged or routed packets
- RFC2364 PPP over AAL5
- IPoA, PPPoA, PPPoE, Multiple PPPoE sessions on single PVC, PPPoE pass-through, PPPoE filtering of on-PPPoE packets between WAN and LAN
- Transparent bridging between all LAN and WAN interfaces
- 802.1q VLAN support
- · Spanning Tree Algorithm
- · IGMP Proxy V1/V2
- · Static route, RIP v1/v2
- · DHCP Server/Client/Relay
- · DNS Relay, Dynamic DNS
- · ARP, RARP

Security Functions

- · PAP, CHAP, TCP/IP/Port filtering rules
- · Port triggering/Forwarding, Packet and MAC address filtering
- · Access control, SSH

Application Passthrough

PPTP, L2TP, IPSec, VoIP, Yahoo messenger, ICQ, RealPlayer, NetMeeting, MSN, X-box, etc

Power Supply

· 100 Vac -220 Vac, 18Vdc/500mA

Environment Condition

- · Operating temperature: 0 ~ 50 degrees Celsius
- Relative humidity: 5 ~ 95% (non-condensing)

Dimensions

· 92mm(W) X 34mm(H) X 114mm(D)

Kit Weight

1* CT-5071T, 1*RJ11 cable, 1*RJ45 cable, 1*power adapter, 1*CD-ROM = 0.65 kg

Note: Specifications are subject to change without notice



Taiwan: 3f-1, No.10, Lane 609, Chung Hsin Road Section 5, San Chung, Taipei, Taiwan 24159 Tel: 886-22999-2861 Fax: 886-2-2999-8497

NO.88 East Qian.Jin Road,Kunshan City,JiangSu,China Tel: 86-512-57383156, 86-512-57383157, 86-512-57384515 Fax: 86-512-57383155

Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain Tel: 34-917990403 Fax: 34-913510999

UK: 566 Chiswick High Road Building 3, Chiswick Park Chiswick - London W4 57A UK
Tei: 44-0-8453701031
Fax: 44-0-8453701032

France:

France: 87, Rue du Gouverneur Général Félix Eboué 92130 Issy-les-Moulineaux, France Tel: 33-1-70715700 Fax: 33-1-70715701

Czech Republic: TOKOVO Jankovcova Tel: 420-266-782040 Fax: 420-266-782990 va 1518/2, 170 00, Prague 7, Czech Republic

USA & Canada:

16 Goodyear, Suite 120, Irvine, CA 92618 Tel: 1-949-7539640 Fax: 1-949-7539020

Brazil:

Al. Campinas, 977 - 7°. Floor - Room 71 / 72 - Jardins Zip Code: 01404-001 - São Paulo - SP - Brazil Tel: 00 55 11 3052-2295 Fax: 00 55 11 3052-2295

Meriano Escobedo 396 Office 503 Colonia Anzures, Deleg. Miguel Hidalgo 11590 Distrito Federal México Tel: +52 (55) 4623-1516