



WIRELESS N 150 ADSL2+ 4-PORT ETHERNET ROUTER

HIGH-SPEED ADSL2/2+ INTERNET CONNECTION

Latest ADSL2/2+ standards provide Internet transmission of up to 24Mbps downstream, 1Mbps upstream

HIGH-PERFORMANCE WIRELESS

Wireless N 150 technology is ideal for high-speed wireless connection, complete compatibility with 802.11b/g wireless devices

TOTAL SECURITY & QoS

Firewall protection from Internet attacks, user access control, WPA/WPA2 wireless security and priority queues for smooth VoIP traffic/streaming multimedia



HIGH-SPEED INTERNET

The Wireless N 150 ADSL2+ 4-Port Ethernet Router is a versatile, high-performance remote router for home and the small office. With integrated ADSL2/2+ supporting up to 24Mbps download speed, firewall protection, Quality of Service (QoS), draft 802.11n wireless LAN and 4 Ethernet switch ports, this router provides all the functions that a home or small office needs to establish a secure and high-speed remote link to the outside world.

ULTIMATE WIRELESS CONNECTION

The Wireless N 150 ADSL2+ 4-Port Ethernet Router provides wireless speeds that are many times faster than 802.11g. Maximize wireless performance and stay connected from virtually anywhere at home and in the office. The DSL-2730B supports WPA/WPA2 and WEP data encryption methods for flexible user access security.

FIREWALL PROTECTION & QoS

Security features prevent unauthorized access to the home and office network from wireless devices or from the Internet. The Wireless N 150 ADSL2+ 4-Port Ethernet Router provides firewall security, such as Stateful Packet Inspection (SPI) and hacker attack logging. SPI inspects the contents of incoming packets before they are allowed in, while hacker logging helps to protect your network against Denial of Service (DoS) attacks. For Quality of Service (QoS), the router supports priority queues to enable a group of home or office users to experience the benefit of a smooth network connection without concern of traffic congestion.

COMPATIBILITY ASSURANCE

The Wireless N 150 ADSL2+ 4-Port Ethernet Router is backward compatible with existing 802.11b and 802.11g wireless equipment, ensuring compatibility with a wide range of wireless devices. In addition, this router includes four Ethernet ports ready for you to connect Ethernet-enabled PCs, print servers and other devices.

WHAT THIS PRODUCT DOES

This Wireless N 150 ADSL2+ 4 port Ethernet Router connects a group of users to the Internet, allowing multiple computers at home or the office to share an integrated high speed ADSL2+ connection. It features 4 built-in Ethernet ports, firewall protection, and QoS for smooth and secure transfer of photos, files, music, video, and e-mail over the Internet.

GET HIGH ADSL AND WIRELESS PERFORMANCE

Connect to your ADSL connection at up to 24Mbps downstream and 1Mbps upstream. High speed performance gives you smooth media streaming, so you can watch TV, listen to live music, broadcast over the Internet, and experience clear Internet phone calls. Wireless N 150 technology allows you to connect to 802.11n wireless devices at up to 150Mbps¹, so you can make full use of your broadband connection.

TECHNICAL SPECIFICATIONS

DEVICE INTERFACES

- RJ-11 ADSL port
- RJ-45 10/100BASE-TX Ethernet ports with auto MDI/MDIX
- Built-in Wireless N 150
- Factory reset button
- WPS button
- Wireless on/off switch
- Power on/off switch

WIRELESS LAN

- 802.11b/g standards, Wireless N 150
- Optional 802.11n capabilities
- Up to 150Mbps throughput
- Frequency range: 2.4GHz to 2.484GHz
- 64/128 bits WEP data encryption
- WPA/WPA2 (Wi-Fi Protected Access) security
- Multiple SSID
- 802.11e Wireless QoS (WMM/WME)
- MAC address-based access control

WIRELESS TRANSMISSION POWER²

- 17dBm +/- 2dBm

ADSL STANDARDS

- ADSL standards: Multi-mode, ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A, ITU G.994.1 (G.hs)
- ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A/L/M, ITU G.992.4 (G.lite.bis) Annex A
- ADSL2+ standards: ITU G.992.5 Annex A/L/M

ADSL DATA RATES

- G.dmt: 8Mbps downstream, 832Kbps upstream
- G.lite: 1.5Mbps downstream, 512Kbps upstream
- ADSL2: 12Mbps downstream, 1Mbps upstream
- ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM & PPP PROTOCOLS

- ATM Forum UNI3.1/4.0 PVC (up to 16PVCs)
- ATM Adaptation Layer Type 5 (AAL5)
- ATM QoS (Traffic Shaping)
- Bridged or routed Ethernet encapsulation
- VC and LLC based multiplexing
- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- ITU-T I.610 OAM F4/F5

ROUTER FEATURES

- WAN/LAN Switchable Port
- NAT (maximum 4096 NAT sessions)
- DHCP server/client/relay
- Static Routing, RIP v.1, v.2
- Universal Plug and Play (UPnP) Compliant
- Dynamic Domain Name System (DDNS)
- Virtual Server
- SNTP, DNS proxy and IGMP proxy

FIREWALL

- Built-in NAT firewall
- Stateful Packet Inspection (SPI)
- DoS attacks prevention
- Packet filtering (IP/ICMP/TCP/UDP)
- Intrusion Detection System (IDS)
- DMZ

VIRTUAL PRIVATE NETWORK (VPN)

- Multiple PPTP/IPSec/L2TP pass-through

DEVICE CONFIGURATION/MANAGEMENT

- Installation Wizard
- Web-based GUI for configuration, firmware upgrade
- Code lock to prevent improper firmware upgrade
- Telnet
- Syslog monitoring
- TR-069 Client
- WPS

QUALITY OF SERVICE

- LAN to WAN traffic prioritization/Classification
- 802.1p (0 to 7) traffic prioritization
- Traffic Shaping

SECURITY

- IGMP Snooping with 32 Multicast groups
- PVC/VLAN port mapping (bridge mode)
- Parental Control (URL blocking, scheduling)

POWER INPUT

- Through 12VAC 1A external power adapter

DIAGNOSTIC LEDS

- Power
- LAN (1 to 4)
- WLAN
- DSL
- Internet
- WPS

DIMENSIONS

195.16 x 115.93 x 36.55 mm
(7.7 x 4.6 x 1.4 inches)

OPERATING TEMPERATURE

0° to 40° C (32° to 104° F)

STORAGE TEMPERATURE

-20° to 70° C (-4° to 158° F)

OPERATING HUMIDITY

5% to 95% non-condensing

Certifications

- CE (EN55022/EN55024/EN300 328/EN301 489)

¹ Maximum wireless signal rate based on IEEE 802.11g standard and 802.11n draft specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

² Typical transmission power; transmission power setting varies according to country.

The devices described herein are in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC. Product specifications, size, and shape are subject to change without notice. Actual product appearance may differ from that depicted on packaging. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks are the property of their respective owners.

