

Start a Wireless Network With Up To 4X the Range and 12X the Speed!



The Wireless-N Broadband Router is really three devices in one box. First, there's the Wireless Access Point, which lets you connect to the network without wires. There's also a built-in 4-port full-duplex 10/100 Switch to connect your wired-Ethernet devices together. Finally, the Router function ties it all together and lets your whole network share a high-speed cable or DSL Internet connection.

The Access Point built into the Router uses the very latest wireless networking technology, Wireless-N (draft 802.11n). By overlaying the signals of multiple radios, Wireless-N's "Multiple In, Multiple Out" (MIMO) technology multiplies the effective data rate. Unlike ordinary wireless networking technologies that are confused by signal reflections, MIMO actually uses these reflections to increase the range and reduce "dead spots" in the wireless coverage area. The robust signal travels farther, maintaining wireless connections up to 4 times farther than standard Wireless-G.

With Wireless-N, the farther away you are, the more speed advantage you get. It works great with standard Wireless-G and -B equipment, but when both ends of the wireless link are Wireless-N, the router can increase the throughput even more by using twice as much radio band, yielding speeds up to 12 times as fast as standard Wireless-G. But unlike other speed-enhanced technologies, Wireless-N can dynamically enable this double-speed mode for Wireless-N devices, while still connecting to other wireless devices at their respective fastest speeds. In congested areas, the "good neighbor" mode ensures that the Router checks for other wireless devices in the area before gobbling up the radio band.

To help protect your data and privacy, the Router can encode all wireless transmissions with industrial-strength 256-bit encryption. It can serve as your network's DHCP Server, has a powerful SPI firewall to protect your PCs against intruders and most known Internet attacks, and supports VPN pass-through. Configuration is a snap with the web browser-based configuration utility.

The incredible speed of Wireless-N makes it ideal for media-centric applications like streaming video, gaming, and Voice over IP telephony, and gives you plenty of headroom to run multiple media-intense data streams through the network at the same time, with no degradation in performance. With the Linksys Wireless-N Broadband Router at the center of your home or office network, you can share a high-speed Internet connection, files, printers, and multi-player games, and run media-intensive applications at faster than 10/100 wired network speeds, without the hassle of stringing wires!

Internet-sharing Router and 4-port Switch, with a built in speed and range enhanced Wireless Access Point MIMO technology uses multiple radios to create a robust signal that travels up to 4 times farther and reduces dead spots Up to 12 times faster than Wireless-G, but also works great with Wireless-G and -B devices Wireless signals are protected by up to 256-bit encryption, and your network is protected from Internet attacks by a powerful SPI firewall

Wireless-N



Broadband Router

Product Data

CISCO SYSTEMS

Wireless-N

Broadband Router

Features

- Complies with IEEE draft 802.11n standards
- Blazing fast wireless speeds for high bandwidth applications such as video streaming or file sharing
- Unsurpassed wireless security with 256-bit encryption
- Expanded wireless coverage. Up to 4X the range of 802.11g products
- All LAN ports support auto-crossover (MDI/MDI-X)—No need for crossover cables
- Device can be placed vertically or horizontally

Specifications

Model	WRT300N	
Standards	Draft 802.11n, 802.11g, 802.11b, 802.3, 802.3u	
Ports	Power, Internet, Ethernet	
Button	Reset	
Cabling Type	CAT5	
LEDs	Power, Internet, Ethernet (1-4), Wireless	
Number of Antennas	3	
Transmit Power	17 dBm	
Antenna Gain	2 dBi	
UPnP able/cert	able	
Security Features	Up to 256-bit wireless encryption	
Security Key Bits	64, 128, 256	
Environmental		
Dimensions	7.40" x 1.57" x 6.93" (188 x 40 x 176 mm)	
Weight	18.60 oz. (0.527 kg)	
Power	12 V, 1 A	
Certification	FCC, CE, IC-03	
Operating Temp.	0° C to 40° C (32° F to 104° F)	
Storage Temp.	-20° C to 70° C (-4° F to 158° F)	
Operating Humidity	10% to 85% Non-Condensing	
Storage Humidity	5% to 90% Non-Condensing	

Linksys A Division of Cisco Systems, Inc.	Minimum Requirements	Package Contents
121 Theory Irvine, CA 92617 USA E-mail: sales@linksys.com	Internet Explorer 5.5 or Firefox 1.0 CD-ROM Drive Windows 2000 or XP	Wireless-N Broadband Router Setup CD-ROM with Norton Internet Security User Guide on CD-ROM
support@linksys.com Web: http://www.linksys.com	Network Adapter	Ethernet Network Cable Power Adapter
Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.		

Check the product package and contents for specific features supported. Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2006 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.