NETCOMM LIBERTY<sup>™</sup> SERIES

# **3G WiFi Router**






### **KEY FEATURES**

- O Wireless router with built-in multi-mode 3G/Next G<sup>™</sup> modem and 4 network ports
- Dual antenna diversity for optimal cellular reception
- O Connects to the Internet via the 3G/Next G<sup>™</sup> mobile broadband network
- Shares a single 3G mobile broadband connection with 4 wired and multiple wireless-enabled devices such as laptops, PCs, iPads and smart phones
- O Creates your personal WiFi zone for convenient wireless Internet access
- Provides download speeds of up to 7.2 Mbps (HSDPA) and 5.76 Mbps upload (HSUPA)<sup>2</sup>
- Wide coverage through tri-band HSDPA/HSUPA/UMTS (850/1900/2100 MHz) and quad-band EDGE/GPRS/GSM (850/900/1800/1900 MHz)
- Firewall and advanced wireless encryption WPA2/WPA
- Simple user-friendly setup and configuration interface

Model Code/ Part Number	Description	APN Code
3G19W-AU	NetComm 3G WiFi Router	9317773014501

## **3G WiFi Router**





## **Compact and Portable - Wireless Internet For** Office and Home.

The Netcomm 3G19W creates a secure wireless network, providing Internet access by using the 3G/Next G<sup>™</sup> network. Simply connect the 3G19W to an electrical power outlet, insert an active SIM card of your mobile broadband provider and get access to a 3G/HSPA Internet connection within seconds.

Connect up to four devices via the network ports and multiple wireless-enabled devices such as laptops, iPads, home cinema systems and gaming consoles. The built-in Wireless access point provides W-LAN data speeds up to 54 Mbps<sup>1</sup>.

The NetComm 3G19W is ideal for mobile businesses, temporary office setups and for home users who don't want a fixed line connection.

- 1 Maximum wireless signal rate and coverage values are derived from IEEE Standard 802.11g and 802.11n specifications. Actual wireless speed and coverage are dependent on network and environmental conditions included but not limited to volume of network traffic, building materials and construction/layout.
- Speeds are dependent on network conditions and coverage. See coverage maps of your carrier or mobile service provider for 2 more details

#### HARDWARE

- 11x LEDs Power, LAN, WiFi, Internet, 3G/2G, Signal Strength
- 4x LAN Ports (RJ-45 10/100 Ethernet)
- 2x Cellular Antenna Ports (SMA-M)
- 1x WiFi Antenna Port (SMA-F)
- 2x Buttons: Power On/Off, Reset

#### **3G/2G WAN SPECIFICATIONS**

#### MULTI-MODE MODEM

- Sierra Wireless MC8790
- Qualcomm MSM6290<sup>™</sup> chipset
- Complies with the 3GPP Release 5 and Release 6 UMTS Specification

#### NETWORK SUPPORT

- 3G/UMTS Tri-band: 850/1900/2100 MHz
- 2G/GSM Quad-band: 850/900/1800/1900 MHz

#### DATA RATE

- HSDPA Category 8 (up to 7.2 Mbps downlink)<sup>1</sup> •
- HSUPA Category 6 (up to 5.76 Mbps downlink)<sup>1</sup> EDGE/GPRS Multi Slot Class 12 (up to 236 Kbps)1

PO Box 1200, Lane Cove NSW 2066

Sydney, Australia ABN 85 002 490 486

- ANTENNA DIVERSITY
- 2x Cellular Antennas (Main, Rx Div)

NETCOMM LIMITED

• Receive Diversity 850/2100 MHz

#### WIRELESS LAN SPECIFICATIONS

FREQUENCY BAND

#### 2.400~2.484 GHz

- ANTENNA
- 1x WiFi Antenna (1T/1R) WIRELESS STANDARDS
- IEEE 802.11g

#### IFFF 802.11b

- WIRELESS SECURITY
- WEP 64/128-bit Wired Equivalent Privacy
- WPA/WPA2 Wi-Fi Protected Access
- IEEE 802.1x Authentication .
- MAC Address Filtering

#### CHANNELS

- 11 Channels (US, Canada)
- 13 Channels (Europe, Australia)

#### NETWORK SUPPORT

- ROUTING
- Static Route
- NAT /PAT Network/Port Address Translation DMZ
- DHCP Client/Server/Relay
- DNS ProxyDynamic DNS

**AUSTRALIAN ENQUIRIES** 

E: sales@netcomm.com.au

W: www.netcomm.com.au

P: (02) 9424 2070

F: (02) 9424 2010

### NEW ZEALAND ENQUIRIES

P: (09) 448 5548 F: (09) 448 5549 E: sales@netcomm.co.nz W: www.netcomm.co.nz

#### FIREWALL MAC/IP Address/Port Filtering •

- Stateful Packet Inspection (SPI)
- Packet filtering •
  - Denial of Service Protection (DoS)
  - AUTHENTICATION PROTOCOLS • PAP, CHAP
- VPN
- VPN Pass-through (IPsec/PPTP/L2TP)
- SYSTEM MANAGEMENT
- Configuration via Web Browser (HTTP)
- Configuration Backup and Restoration Firmware Upgrade via HTTP, TFTP client/server or FTP
- SNMP / SNTP (Time Zone)/ Telnet
- **ENVIRONMENTAL AND PHYSICAL**
- Operating Temperature: 0 ~ 50 °C ٠
- Relative Humidity: 5 ~ 90% (non-condensing)
- Dimensions: 215 mm (L) x 37 mm (W) x 145 mm (H)
- DC Input Voltage: 12 V/ 1.5 A
  - INTERNATIONAL ENQUIRIES P: +61 2 9424 2070 F: +61 2 9424 2010 E: int.sales@netcomm.com.au W: www.netcommlimited.com
- Trademarks and registered trademarks are the property of NetComm Limited or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the actual product