

>Incredible wireless high speed up to 300Mbps, great for faster downloading,

Internet calling and HD video streaming

>MIMO high gain 5dBi antennas providing maximum range and stable connections

>Various WAN connection types in Router mode- DHCP, Static IP, PPPoE, WISP

>Multiple wireless modes- AP, Repeater, AP+WDS, WDS, Client

>Multi-SSID providing additional separate network for guests and friends

>Easy wireless security setup at a push of the WPS button

>Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably

>Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time

What it does:

The netis WF2409D 300Mbps Wireless N Router is a combined wired and wireless device for SOHO network applications. It's compatible with 802.11b/g/n devices and provides the wireless transfer speed up to 300Mbps, offering a powerful performance on faster downloading, Internet calling and HD video streaming. Bundled with three 5dBi high gain detachable antennas, it ensures a better wireless coverage and allows you to enjoy the wireless freedom anywhere around your home.

Specification:

Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	20dBm(MAX)
Data Transfer Rate	802.11n: 40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP, WDS, AP+WDS, Repeater, Client, Multiple AP
Wireless Security	64/128-bit WEP WPA-PSK/WPA2-PSK (TKIP/AES) SSID Broadcast Enable/ Disable Wireless MAC Filtering

Software	
WAN Type	DHCP(Dynamic IP), PPPoE, Static IP, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Application Priority, Bandwidth Control
Access Control	IP/MAC/Domain filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, Firmware upgrade
Others	
Certification	FCC, CE
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

1 * Quick Installation Guide

1 * Power Adapter

Topological Graph:

Package



1 *WF2409D

1 * Cradle

1 * Ethernet Cable