



## 300Mbps Wireless N ADSL2/2+ Modem Router TEW-635BRM(V1.0R)

The 300Mbps Wireless N ADSL 2/2+ Modem Router delivers both Internet access and a high-performance wireless n network in a single solution.

No need to buy a separate modem and router. Install this device easily and surf the Internet, download files, play games and talk online with 300Mbps wireless n technology.



Connect computers, gaming consoles, media players and storage devices to the built in 4-port switch. The latest in wireless encryption and a double firewall protect your valuable data. Advanced antenna technology (MIMO) delivers broad coverage and minimizes dead spots. One-touch Wi-Fi Protected Setup (WPS) synchronizes WPS peripheral devices at the touch of a button.

## FEATURES

- Wi-Fi compliant with IEEE 802.11n draft 2.0 standard
- Router + modem or modem only mode
- Compliant with ADSL, ADSL2 and ADSL2+
- Auto detection for PPPoE, PPPoA and IPoA Internet connection types
- 2 fixed 2dBi antennas support high speed performance and expanded coverage with MIMO technology
- Wireless Distribution System (WDS)
- Multiple SSID support with isolation
- Wireless on/off button
- Power on/off button
- Backwards compatible with IEEE 802.11b/g devices
- Supports Wi-Fi Protected Setup (WPS) to quickly connect wireless peripheral devices
- Universal Plug and Play (UPnP) and Application Level Gateway (ALG) support for Internet applications such as e-mail, FTP, gaming, remote desktop, Net Meeting and telnet
- Internet Access Control via MAC Address, URL and IP Filtering
- Easy Web-browser configuration and remote management
- Wi-Fi Multimedia (WMM) Quality of Service (QoS) supported
- Multiple VPN Pass-through sessions for IPSec, PPTP and L2TP
- Advanced wireless encryption : WEP, WPA-PSK, WPA2-PSK and 802.1x
- 3-year limited warranty

\*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

# 300Mbps Wireless N ADSL2/2+ Modem Router

## TEW-635BRM(V1.0R)

### SPECIFICATIONS

| Hardware                  |   |
|---------------------------|---|
| <b>Standards</b>          | <ul style="list-style-type: none"><li>• Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX) • Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n (draft 2.0)</li><li>• ADSL : ANSI T1.413 and multi-mode</li><li>• ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 G.lite, ITU G.992.3 Annex A ADSL2, ITU G.992.3 Annex A DELT, ITU G.992.3 Annex L READSL2, ITU G.992.5 Annex A ADSL2+, ITU G.994.1 (G.hs) ver.3</li></ul>   |
| <b>Protocol</b>           | <ul style="list-style-type: none"><li>• DHCP (Client/Server), SMTP, NTP</li></ul>   |
| <b>VPN Pass-Through</b>   | <ul style="list-style-type: none"><li>• PPTP, IPSec, L2TP (up to 100 sessions)</li></ul>  |
| <b>ATM</b>                | <ul style="list-style-type: none"><li>• Supports TM Cell over AAL5, UBR/CBR/VBR, VPI range (0-255) and VCI range (32 ~65535 ), multiple-PVC and OAM F4/F5 loopback</li><li>• Payload encapsulation<ul style="list-style-type: none"><li>• RFC2684 (RFC1483/2684), Multiprotocol over ATM</li><li>• RFC2684 (RFC1483/2684), Bridge mode</li><li>• RFC2364, PPP over ATM (CHAP and PAP supported)</li><li>• RFC2516, PPP over Ethernet</li></ul></li><li>• Supports auto-detection for VPI/VCI (VPI :0 ~10, VCI : 32 ~ 90) and multiplexing method (VC/LLC based)</li></ul> |
| <b>Firewall</b>           | <ul style="list-style-type: none"><li>• NAT Firewall with ALGs, Denial of Service(DoS) attack firewall, email alerts and log, access control, port forwarding, port range forwarding and schedule-based URL filtering</li></ul>   |
| <b>Management</b>         | <ul style="list-style-type: none"><li>• Web-browser configuration or remote management</li></ul>  |
| <b>Routing</b>            | <ul style="list-style-type: none"><li>• Cross Segment Static Route, RIP1, RIP2</li></ul>  |
| <b>WAN</b>                | <ul style="list-style-type: none"><li>• 1 x RJ-11 port</li></ul>  |
| <b>LAN</b>                | <ul style="list-style-type: none"><li>• 4 x 10/100Mbps Auto-MDIX port</li></ul>   |
| <b>WPS Button</b>         | <ul style="list-style-type: none"><li>• Wi-Fi Protected Setup button</li></ul>  |
| <b>Wireless Button</b>    | <ul style="list-style-type: none"><li>• On/off wireless</li></ul>   |
| <b>Power Button</b>       | <ul style="list-style-type: none"><li>• On/off power</li></ul>  |
| <b>LED</b>                | <ul style="list-style-type: none"><li>• Power, Status, 10/100Mbps, Wireless, ADSL, Internet and WPS</li></ul>   |
| <b>Supported Browser</b>  | <ul style="list-style-type: none"><li>• Internet Explorer v5.5 or higher, Netscape 7.0 or higher, Mozilla 1.6 or higher</li></ul>   |
| <b>Power</b>              | <ul style="list-style-type: none"><li>• 12VDC, 1A external power adapter</li></ul>  |
| <b>Power Consumption</b>  | <ul style="list-style-type: none"><li>• 6W (max)</li></ul>  |
| <b>Dimensions (LxWxH)</b> | <ul style="list-style-type: none"><li>• 175 x 130 x 30mm (6.90 x 5.12 x 1.18in.)</li></ul>  |
| <b>Weight</b>             | <ul style="list-style-type: none"><li>• 255g (8.99oz)</li></ul>   |
| <b>Temperature</b>        | <ul style="list-style-type: none"><li>• Operating: 0°C ~ 40°C (32°F ~ 104°F); Storage: -20°C ~ 70°C (-4°F ~ 158°F)</li></ul>  |
| <b>Humidity</b>           | <ul style="list-style-type: none"><li>• Max 95% (non-condensing)</li></ul>  |
| <b>Certification</b>      | <ul style="list-style-type: none"><li>• FCC, CE</li></ul>   |



# 300Mbps Wireless N ADSL2/2+ Modem Router TEW-635BRM(V1.0R)

## SPECIFICATIONS

| Wireless                  |   |
|---------------------------|---|
| Frequency                 | • 2.412 ~ 2.4835 GHz  |
| Modulation Technique      | • 802.11n: BPSK, QPSK, 16QAM, 64QAM, OFDM • 802.11g: BPSK, QPSK, 16-QAM, 64-QAM, OFDM<br>• 802.11b: DBPSK, DQPSK, CCK                               |
| Antenna                   | • 2 x fixed 2dBi antennas   |
| Data Rate (auto fallback) | • 802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps • 802.11n: up to 300Mbps<br>• 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps |
| Output Power              | • 802.11b: 17dBm $\pm$ 1.5 (typical) • 802.11g: 15dBm $\pm$ 1.5 (typical) • 802.11n: 12.5dBm $\pm$ 1.5 (typical)                                    |
| Receiving Sensitivity     | • 802.11b: -86 $\pm$ 1.5 dBm (typical) • 802.11g: -70 $\pm$ 1.5 dBm (typical) • 802.11n: -69 $\pm$ 1.5 dBm (typical)                                |
| Encryption                | • 64/128-bit WEP (Hex), WPA-PSK(TKIP), WPA2-PSK(AES), WPA-PSK/WPA2-PSK mixed (TKIP/AES) and WPA-802.1x  |
| Channels                  | • 1 ~ 14 Channel (Universal Domain Selection)   |

## NETWORKING SOLUTIONS

### 300Mbps Wireless N ADSL2/2+ Modem Router (TEW-635BRM)



## PACKAGE CONTENTS

- TEW-635BRM
- Multi-Language Quick Installation Guide
- CD-ROM (User's guide)
- 1 x RJ-45 Ethernet cable (1.5m,4.92ft.)
- 1 x RJ-11 cable (0.9m,3ft.)
- Power adapter (12VDC, 1A)

## RELATED PRODUCTS

|           |                                    |
|-----------|------------------------------------|
| TEW-624UB | 300Mbps Wireless N USB 2.0 Adapter |
| TEW-621PC | Wireless N PC Card                 |
| TEW-623PI | 300Mbps Wireless N PCI Adapter     |

## ORDERING INFORMATION

**TRENDnet**<sup>®</sup>

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: [www.trendnet.com](http://www.trendnet.com)

Email: [sales@trendnet.com](mailto:sales@trendnet.com)

To Order Please Call:

**1-888-326-6061**

