



**Economical solution provides Voice over the Internet using conventional tele-phones**

**Provides two FXS ports for two VoIP channels**

**Uses industry-standard Session Initiation Protocol (SIP)**

**Clear, natural-sounding voice quality**

**Supports remote delivery of firmware updates**

**Supports automatic provisioning by service providers**

**Supports Quality of Service (QoS)**

**Supports STUN (Simple Traversal of UDP over NATs)**

**Supports advanced telephone services including CLASS features, Call Waiting, Caller Identification, Call Transfer, Call Hold, Call Forwarding, Distinctive Ring, and Voice Message Waiting Indication**



# Zoom Voice over IP Telephone Adapter

## Model 5821F with G.711, iLBC and G.729 Codecs

The Model 5821F Voice over IP Telephone Adapter allows standard analog telephones to make and receive calls over a broadband Internet connection. The 5821F has two FXS ports to allow two VoIP channels. Simply plug one or two conventional or cordless phones into a Model 5821F and then plug the telephone adapter into a broadband-connected router or Internet gateway. Up to five and often more attached phones can be rung simultaneously on each FXS port using the built-in ring generator.

The Models 5821F supports industry-standard Sessions Initiation Protocol (SIPv2) and work with a wide range of service providers and SIP-based VoIP equipment.

Voice over IP Service providers can deliver a rich variety of advanced telephone services through the Model 5821F including CLASS features such as Call Waiting, Caller Identification, Call Transfer, Call Hold, Call Forwarding, Distinctive Ringing, and Voice Message Waiting Indication.

The VoIP telephone adapter can be configured remotely using a TFTP or HTTP download from the service provider and updates to the firmware can be automatically delivered. Local configuration is done with a browser-based graphical user interface.

The Model 5821F is built and supported by Zoom Technologies, a publicly traded company with over 30 years of experience in telephony and data communications.

### Specifications

- |                                |  |
|--------------------------------|--|
| Analog Telephone Ports         | <ul style="list-style-type: none"><li>• Two FXS type Loop-start interface ports</li><li>• Up to 5 REN (Ringer Equivalence Number) for support of up to 5 and often more typical telephones for each FXS port</li><li>• Programmable Ring Patterns</li><li>• Call progress tones supported: Initial dial tone, Secondary dial tone, Stuttered dial tone, Message waiting dial tone, Call forward dial tone, Pre-ringback dial tone, Ring back tone, Call waiting tone, Call holding tone, Call disconnect tone, Call conference tone, Busy tone, Reorder tone (network busy/fast busy), Off hook warning.</li></ul> |
| Status Indicators              | <ul style="list-style-type: none"><li>• Power, LAN link, VoIP ready, VoIP call-in-progress, Voice message waiting</li></ul>  |
| Voice over IP (VoIP) Protocols | <ul style="list-style-type: none"><li>• SIPv2 - Session Initiation Protocol (RFC 3261, 3262, 3263, 3264)</li><li>• SDP - Session Description Protocol (RFC 2327)</li><li>• RTP - Real Time Protocol (RFC 1889, 1890)</li><li>• RTCP - Real-Time Control Protocol (RFC 1889)</li><li>• X-NSE - Tone Events for SIP/RTP (RFC 2833)</li><li>• AVT - Tone Events for SIP/RTP (RFC 2833)</li><li>• Power-on Auto Registration</li><li>• Re-registration with SIP Proxy Server</li><li>• SIP over UDP</li><li>• SIP authentication (HHP Digest with MD5)</li></ul>   |

## Voice over IP Telephone Adapters

### Specifications (continued)

Network Protocols	<ul style="list-style-type: none"> <li>• IPv4 - Internet Protocol Version 4 (RFC 791)</li> <li>• TCP - Transmission Control Protocol (RFC 793)</li> <li>• UDP - User Datagram Protocol (RFC 768)</li> <li>• ICMP - Internet Control Message Protocol. (RFC 792)</li> <li>• RARP - Reverse Address Resolution Protocol (RFC 903)</li> <li>• ARP - Address Resolution Protocol (RFC 826)</li> <li>• DNS - Domain Name Server</li> <li>• DHCP Client - Dynamic Host Control Protocol (RFC 2131)</li> <li>• NTP - Network Time Protocol (RFC 1305)</li> <li>• SNTP - Simple Network Time Protocol (RFC 2030)</li> <li>• STUN - Simple Traversal of UDP over NATs (RFC 3789)</li> <li>• HTTP - HyperText Transfer Protocol</li> <li>• TFTP - Trivial File Transfer Protocol (RFC 1350)</li> </ul>
Voice Codecs	<ul style="list-style-type: none"> <li>• G.711 - Pulse Code Modulation</li> <li>• G.729</li> <li>• iLBC (Internet Low Bitrate Codec)</li> </ul>
Telephony	<ul style="list-style-type: none"> <li>• Q.24 DTMF generation and detection</li> <li>• Configurable tone frequency and on/off cadence generation</li> <li>• Caller ID Generation and Detection (Type I and II)</li> <li>• 3-way conference calling with local mixing</li> <li>• Message waiting indicator light</li> <li>• G.711 Fax Pass-through</li> <li>• CLASS feature support</li> <li>• G.165, G.168 compliant line echo cancellation</li> <li>• Nonlinear echo cancellation</li> <li>• Double talk detection</li> </ul>
Quality of Service Support	<ul style="list-style-type: none"> <li>• Layer 2 Class-of-Service (COS) Tagging (802.1P)</li> <li>• Layer 2 (802.1Q VLAN)</li> <li>• Layer 3 Type-of-Service (ToS) Tagging (RFC 791/1349)</li> <li>• Layer 3 Diffserv (RFC 2475)j Ofo</li> </ul>
Security	<ul style="list-style-type: none"> <li>• Provisioning/Configuration/Authentication</li> <li>• Password-protected, Web based administration</li> <li>• ARC4 Encryption for TFTP Configuration Profiles</li> <li>• Authentication (Digest using MD5)</li> </ul>
Size	<ul style="list-style-type: none"> <li>• 14.6 cm X 11.2 cm X 2.8 cm (5.7 inches X 4.4 inches X 1.1 inches)</li> </ul>
Minimum Requirements	<ul style="list-style-type: none"> <li>• High speed Internet connection (typically a DSL or data-over cable connection)</li> <li>• A router or gateway to share the broadband Internet connection</li> <li>• A Touchtone telephone (conventional analog phone) or a fax machine</li> </ul>
Regulatory Approvals	<ul style="list-style-type: none"> <li>• FCC Part 15B, ICES-003, IC LS-03, CE, CSA (C,US), RoHS compliant</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>• Two year limited warranty</li> </ul>



#### International Headquarters

Zoom Telephonics, Inc.  
207 South Street  
Boston, MA 02111  
USA  
Tel: 617 423-1072  
Fax: 617 423-3923

#### European Sales/Support

Zoom Telephonics, Inc.  
Centaur House  
Ancells Business Park  
Ancells Road  
Fleet, Hants  
GU51 2UJ UK  
Tel: +44 (0) 1252 761218  
Fax +44 (0) 1252 761630

#### Ventas América Latina

Zoom Telephonics Inc.  
10237 Clubhouse Turn Rd.  
Wellington, FL, 33449, USA  
Tel. 1-561-357-9339  
Fax 1-561-357-9660

email: [sales@zoom.com](mailto:sales@zoom.com)

Website: [www.zoom.com](http://www.zoom.com)

#### OTCBB: ZMTP

Made in U.S.A.  
©2010 Zoom Telephonics, Inc.,  
207 South Street, Boston, MA 02111  
Zoom is a registered trademark of  
Zoom Telephonics, Inc. Windows XP,  
Windows 98, Windows 2000, Windows  
Me, and NetMeeting are registered  
trademarks of Microsoft Corporation.  
All other registered trademarks and  
trademarks used herein are the  
property of their respective holders.

### Package contents:

- VoIP telephone adapter
- Power adapter
- Quick Start Guide
- Ethernet cable
- Phone cord

