



LevelOne User Manual

WAP-6013

300Mbps Wireless Access Point

Ver. 1.0

Safety

FCC WARNING

This equipment may generate or use radio frequency energy. Changes or modifications to this equipment may cause harmful interference unless the modifications are expressly approved in the instruction manual. The user could lose the authority to operate this equipment if an unauthorized change or modification is made.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- 1) Reorient or relocate the receiving antenna.
- 2) Increase the separation between the equipment and receiver.
- 3) Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- 4) Consult the dealer or an experienced radio/TV technician for help.

CE Declaration of conformity

This equipment complies with the requirements relating to electromagnetic compatibility, EN 55022 class B for ITE, the essential protection requirement of Council Directive 89/336/EEC on the approximation of the laws of the Member States relating to electromagnetic compatibility.

CE Marking Warning

Hereby, Digital Data Communications, declares that this product is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.

The CE-Declaration of Conformity can be downloaded at:
<http://www.levelone.eu/support.php>



NCC Marking Warning

第十二條

型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。

第十四條

低功率射頻電機之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。

前項合法通信，指依電信法規定作業之無線電通信。

低功率射頻電機須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。

General Public License

This product incorporates open source code into the software and therefore falls under the guidelines governed by the General Public License (GPL) agreement.

Adhering to the GPL requirements, the open source code and open source license for the source code are available for free download at

<http://global.level1.com>.

If you would like a copy of the GPL or other open source code in this software on a physical CD medium, LevelOne (Digital Data Communications) offers to mail this CD to you upon request, for a price of US\$9.99 plus the cost of shipping.

Table of Contents

Chapter 1 Introduction	5
1.1 Packing List	5
1.2 Spec Summary Table	5
1. Package Information	6
1.3 Hardware Configuration.....	6
1.5 Procedure for Hardware Installation	8
Chapter 3 Making Configuration	9
3.1 Login to Configure from Wizard	9
3.2 System Status	12
3.3 Advanced	13
Appendix A FAQ and Troubleshooting.....	38
What can I do when I have some trouble at the first time?.....	38
How do I connect router by using wireless?.....	39

IP Address	192.168.1.1
Password	admin
Wireless Mode	Enable
Wireless SSID	LevelOne
Wireless Security	None

Chapter 1 Introduction

Congratulations on your purchase of this outstanding Wireless Broadband Router. This product is specifically designed for Small Office and Home Office needs. It is easy to configure and operate even for non-technical users. Instructions for installing and configuring this product can be found in this manual. Before you install and use this product, please read this manual carefully for fully exploiting the functions of this product.

1.1 Packing List

WAP-6013

Power Adapter

Antenna (x2)

Network Cable

Quick Installation Guide

CD User Manual / Utility / QIG


1.2 Spec Summary Table

Device Interface	
Ethernet LAN	5 x RJ-45 port, 10/100Mbps, auto-MDI/MDIX
Antenna	2dBi detachable dipole antenna (5dbi option available)
WPS Button /Wireless On	For WPS connection and Enable "Wireless Function"
Reset Button	Reset to Factory Default setting
LED Indication	Status / LAN1 ~ LAN5/ WiFi
Power Jack	DC Power Jack, powered via external DC 5V/1A switching power adapter
Wireless LAN (WiFi)	
Standard	IEEE 802.11b/g/n-lite compliance
SSID	SSID broadcast or in stealth mode
Channel	Auto-selection, manually
Security	WEP, WPA-PSK,WPA2-PSK
WPS	WPS (Wi-Fi Protected Setup)
WMM	WMM (Wi-Fi Multimedia)
Functionality	

Routing Protocol	Static route, dynamic route (RIP v1/v2)
Management	SNMP, syslog,
Administration	Web-based UI, remote login, backup/restore setting
Environment & Certification	
Package Information	DC 5V/1A power adapter, Quick Installation Guide
Package Information	Device dimension (mm) 185 x 119 x 32 mm
Operation Temp.	Temp.: 0~40oC, Humidity 10%~90% non-condensing
Storage Temp.	Temp.: -10~70oC, Humidity: 0~95% non-condensing
EMI Certification	CE/FCC compliance
RoHS	RoHS compliance

*Specifications are subject to change without prior notice.

1.3 Hardware Configuration





1.4 LED indicators

	LED status	Description
Status	Green in flash	Device status is working.
LAN LED	Green	RJ45 cable is plugged
	Green in flash	Data access
WiFi LED	Green	WLAN is on
	Green in flash	Data access
	Green in fast flash	Device is in WPS PBC mode
	Green in dark	Wi-Fi Radio is disabled

1.5 Procedure for Hardware Installation

Step 1. Attach the antenna.

- 1.1. Remove the antenna from its plastic wrapper.
- 1.2. Screw the antenna in a clockwise direction to the back panel of the unit.
- 1.3. Once secured, position the antenna upward at its connecting joint. This will ensure optimal reception.



1. Turn off the Power Switch first.

Step 2 Insert the Ethernet cable into LAN Port:

Insert the Ethernet patch cable into LAN port on the back panel of Router, and an available Ethernet port on the network adapter in the computer you will use to configure the unit.

Step 4. Power on Router:

- 4.1. Connect the power adapter to the receptor on the back panel of your Router.



Step 5. Complete the setup.

- 5.1. When complete, the Status LED will flash.

Chapter 3 Making Configuration

This product provides Web based configuration scheme, that is, configuring by your Web browser, such as Mozilla Firefox or or Internet Explorer. This approach can be adopted in any MS Windows, Macintosh or UNIX based platforms.


3.1 Login to Configure from Wizard

Type in the IP Address


(<http://192.168.1.1>)




Type password, the default is
“admin” and click ‘login’ button.



Press “Wizard” for basic
settings with simple way,
Press “Next” to start wizard.



Step 1:
Set up your system password.



level
English

ADMINISTRATOR'S MAIN MENU Status Wizard Advanced Logout

Setup Wizard - Setup Login Password [EXIT]


Old Password

New Password

Reconfirm

< Back [Start > Password > LAN > Wireless > Summary > Finish!] Next >

Step 2:
Setup the LAN IP



level
English


ADMINISTRATOR'S MAIN MENU Status Wizard Advanced Logout

Setup Wizard - LAN Settings - LAN IP Address [EXIT]

LAN IP Address 192.168.1.1

< Back [Start > Password > LAN > Wireless > Summary > Finish!] Next >

Step 3:
Set up your Wireless.



level
English

ADMINISTRATOR'S MAIN MENU Status Wizard Advanced Logout

Setup Wizard - Wireless settings [EXIT]


Wireless function Enable Disable

Network ID(SSID) LevelOne


Channel 11

< Back [Start > Password > LAN > Wireless > Summary > Finish!] Next >


Set up your Authentication and Encryption.



Step 4:
Then click Apply Setting.
And then the device will reboot.



Step 5:
Click Finish to complete it.



3.2 System Status

The screenshot displays the LevelOne administrator interface. At the top, there is a navigation bar with the LevelOne logo, a language dropdown set to 'English', and menu items: 'ADMINISTRATOR's MAIN MENU', 'Status', 'Wizard', 'Advanced', and 'Logout'. The main content area is divided into two sections: 'LAN Status' and 'Wireless Status'. The 'LAN Status' section contains a table with three columns: 'Item', 'LAN Status', and an empty column. The 'Wireless Status' section contains a table with three columns: 'Item', 'WLAN Status', and 'Sidenote'. Below the tables are three buttons: 'View Log...', 'Clients List...', and 'Refresh'. At the bottom, the device time is shown as 'Mon Jun 01 03:06:33 2009'.

Item	LAN Status	
LAN IP	192.168.1.1	
Subnet Mask	255.255.255.0	
MAC Address	00-50-18-64-4A-3F	

Item	WLAN Status	Sidenote
Wireless mode	Enable	
SSID	LevelOne	
Channel	11	
Security	WEP	64-bit WEP
MAC Address	00-50-18-64-4A-3F	<input type="button" value="Edit"/>


Device Time: Mon Jun 01 03:06:33 2009

This option provides the function for observing this product's working status:

3.3 Advanced

3.3.1 Basic Setting

Please Select "Advanced Setup" to Setup



The screenshot displays the Level One Administrator's Main Menu. The interface features a blue header with the Level One logo and a language dropdown set to English. Below the header is a navigation bar with tabs for Status, Wizard, Advanced, and Logout. A secondary navigation bar contains icons for BASIC SETTING, SECURITY SETTING, ADVANCED SETTING, and TOOLBOX. On the left, a sidebar lists menu items: Primary Setup, DHCP Server, Wireless, and Change Password. The main content area shows a 'Basic Setting' window with a list of options:

- **Primary Setup**
 - Configure LAN IP.
- **DHCP Server**
 - The settings include Host IP, Subnet Mask, Gateway, DNS, and WINS configurations.
- **Wireless**
 - Wireless settings allow you to configure the wireless configuration items.
- **Change Password**
 - Allow you to change system password.

1. **LAN IP Address:** the local IP address of this device. The computers on your network must use the LAN IP address of your product as their Default Gateway. You can change it if necessary.

ADMINISTRATOR's MAIN MENU		Status	Wizard	Advanced	Logout						
BASIC SETTING		SECURITY SETTING	ADVANCED SETTING	TOOLBOX							
<ul style="list-style-type: none"> Primary Setup DHCP Server Wireless Change Password 	<div style="text-align: right;">[HELP]</div> <table border="1"> <thead> <tr> <th>Item</th> <th>Setting</th> </tr> </thead> <tbody> <tr> <td>▶ LAN IP Address</td> <td>192.168.1.1</td> </tr> <tr> <td>▶ Subnet Mask</td> <td>255.255.255.0</td> </tr> </tbody> </table> <div style="text-align: center;"> <input type="button" value="Save"/> <input type="button" value="Undo"/> </div>					Item	Setting	▶ LAN IP Address	192.168.1.1	▶ Subnet Mask	255.255.255.0
Item	Setting										
▶ LAN IP Address	192.168.1.1										
▶ Subnet Mask	255.255.255.0										

3.3.1.2 DHCP Server

ADMINISTRATOR's MAIN MENU		Status	Wizard	Advanced	Logout																						
BASIC SETTING		SECURITY SETTING	ADVANCED SETTING	TOOLBOX																							
<ul style="list-style-type: none"> Primary Setup DHCP Server Wireless Change Password 	<div style="text-align: right;">[HELP]</div> <table border="1"> <thead> <tr> <th>Item</th> <th>Setting</th> </tr> </thead> <tbody> <tr> <td>▶ DHCP Server</td> <td><input checked="" type="radio"/> Disable <input type="radio"/> Enable</td> </tr> <tr> <td>▶ Lease Time</td> <td>0 Minutes</td> </tr> <tr> <td>▶ IP Pool Starting Address</td> <td>100</td> </tr> <tr> <td>▶ IP Pool Ending Address</td> <td>199</td> </tr> <tr> <td>▶ Domain Name</td> <td></td> </tr> <tr> <td>▶ Primary DNS</td> <td>0.0.0.0</td> </tr> <tr> <td>▶ Secondary DNS</td> <td>0.0.0.0</td> </tr> <tr> <td>▶ Primary WINS</td> <td>0.0.0.0</td> </tr> <tr> <td>▶ Secondary WINS</td> <td>0.0.0.0</td> </tr> <tr> <td>▶ Gateway</td> <td>0.0.0.0 (optional)</td> </tr> </tbody> </table> <div style="text-align: center;"> <input type="button" value="Save"/> <input type="button" value="Undo"/> <input type="button" value="Clients List..."/> <input type="button" value="Fixed Mapping..."/> </div>					Item	Setting	▶ DHCP Server	<input checked="" type="radio"/> Disable <input type="radio"/> Enable	▶ Lease Time	0 Minutes	▶ IP Pool Starting Address	100	▶ IP Pool Ending Address	199	▶ Domain Name		▶ Primary DNS	0.0.0.0	▶ Secondary DNS	0.0.0.0	▶ Primary WINS	0.0.0.0	▶ Secondary WINS	0.0.0.0	▶ Gateway	0.0.0.0 (optional)
Item	Setting																										
▶ DHCP Server	<input checked="" type="radio"/> Disable <input type="radio"/> Enable																										
▶ Lease Time	0 Minutes																										
▶ IP Pool Starting Address	100																										
▶ IP Pool Ending Address	199																										
▶ Domain Name																											
▶ Primary DNS	0.0.0.0																										
▶ Secondary DNS	0.0.0.0																										
▶ Primary WINS	0.0.0.0																										
▶ Secondary WINS	0.0.0.0																										
▶ Gateway	0.0.0.0 (optional)																										

Press “More>>”


1. **DHCP Server:** Choose “Disable” or “Enable.”
2. **Lease time:** This is the length of time that the client may use the IP address it has been Assigned by dhcp server.
3. **IP pool starting Address/ IP pool starting Address:** Whenever there is a request, the DHCP server will automatically allocate an unused IP address from the IP address pool to the requesting computer. You must specify the starting and ending address of the IP

address pool.

4. **Domain Name:** Optional, this information will be passed to the client.
5. **Primary DNS/Secondary DNS:** This feature allows you to assign DNS Servers
6. **Primary WINS/Secondary WINS:** This feature allows you to assign WINS Servers
7. **Gateway:** The Gateway Address would be the IP address of an alternate Gateway.

This function enables you to assign another gateway to your PC, when DHCP server offers an IP to your PC.


8. **DHCP Client List:**



3.3.1.3 Wireless Setting

AP only Mode:

When acting as an access point, this device connects all the stations to a wired network and See the sample application below.



Wireless Setting [HELP]	
Item	Setting
Wireless Module	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Operation Mode	AP Only Mode ▾
AP Number	AP 1 ▾ <input checked="" type="checkbox"/> Enable
Network ID(SSID)	LevelOne
Wireless Mode	b/g/n Mixed mode ▾
SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
WMM	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Channel	11 ▾
Bandwidth	Auto ▾
Security	None ▾
<input type="button" value="Save"/> <input type="button" value="Undo"/> <input type="button" value="WPS Enter..."/> <input type="button" value="Wireless Client List..."/>	

Network ID (SSID): Network ID is used for identifying the Wireless LAN (WLAN). Client stations can roam freely over this product and other Access Points that have the same Network ID. (The factory setting is “default”)

SSID Broadcast: The router will Broadcast beacons that have some information, including ssid so that

The wireless clients can know how many ap devices by scanning function in the network. Therefore, This function is disabled, the wireless clients can not find the device from beacons.

Channel: The radio channel number. The permissible channels depend on the Regulatory Domain.

WPS (WiFi Protection Setup)

WPS is WiFi Protection Setup which is similar to WCN-NET and offers safe and easy way in Wireless Connection.

ADMINISTRATOR's MAIN MENU Status Wizard Advanced Logout

BASIC SETTING SECURITY SETTING ADVANCED SETTING TOOLBOX

- Primary Setup
- DHCP Server
- Wireless
- Change Password


Wi-Fi Protected Setup

Item	Setting
WPS	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Setup	<input checked="" type="radio"/> Current AP PIN <input type="radio"/> Configure Wireless Station
Current PIN of the device	13938789 <input type="button" value="Generate New PIN"/>
WPS state	Idle
Lock Wireless Security	<input checked="" type="checkbox"/> Enable
WPS status	Configured <input type="button" value="Release"/>

Security: Select the data privacy algorithm you want. Enabling the security can protect your data while it is transferred from one station to another.

WDS Hybrid Mode:

While acting as Bridges, Wireless Router 1 and Wireless Router 2 can communicate with each other through wireless interface (with WDS). Thus All Stations can communicate each other and are able to access Internet if Wireless Router 1 has the Internet connection



WDS Setting		[HELP]
Item	Setting	
▶ Wireless Radio	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
▶ Wireless Operation Mode	WDS Hybrid Mode ▼	
▶ Lazy Mode	<input type="checkbox"/>	
▶ Point to Point	<input type="checkbox"/>	
▶ Network ID(SSID)	LevelOne	
▶ SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
▶ Channel	11 ▼	
▶ Security	None ▼	
▶ Remote AP MAC	MAC 1	<input type="text"/>
	MAC 2	<input type="text"/>
	MAC 3	<input type="text"/>
	MAC 4	<input type="text"/>
Scanned AP's MAC <input type="text"/> --- Select one --- ▼ <input type="button" value="Copy to"/> Remote AP MAC <input type="text"/> -- ▼		
SSID	Channel	MAC Address
<input type="button" value="Save"/> <input type="button" value="Undo"/> <input type="button" value="Scan AP"/>		

Wireless Off Schedule: Before turning Off Wireless Radio, the device will detect if Wireless station is online, then depend as Schedule " 01:00~08:30" to disable WiFi service.

Network ID (SSID): Network ID is used for identifying the Wireless LAN (WLAN). Client stations can roam freely over this product and other Access Points that have the same Network ID. (The factory setting is "default")

SSID Broadcast: The router will Broadcast beacons that have some information, including ssid so that

The wireless clients can know how many ap devices by scanning function in the network. Therefore, This function is disabled, the wireless clients can not find the device from beacons.

Channel: The radio channel number. The permissible channels depend on the Regulatory Domain.


Security: Select the data privacy algorithm you want. Enabling the security can protect your

data while it is transferred from one station to another.

Remote AP MAC : Choose “Manual” or scan one AP to copy to item1~4.

WDS(Wireless Distribution System)

The WDS (Wireless Distributed System) function let this access point acts as a wireless LAN access point and repeater at the same time. Users can use this feature to build up a large wireless network in a large space like airports, hotels and schools ...etc.



WDS Setting		[HELP]
Item	Setting	
Wireless Radio	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Wireless Operation Mode	WDS Only Mode ▼	
Point to Point	<input type="checkbox"/>	
Network ID(SSID)	LevelOne	
Channel	11 ▼	
Security	None ▼	
Remote AP MAC	MAC 1	<input type="text"/>
	MAC 2	<input type="text"/>
	MAC 3	<input type="text"/>
	MAC 4	<input type="text"/>
Scanned AP's MAC --- Select one --- ▼ <input type="button" value="Copy to"/> Remote AP MAC -- ▼		
SSID	Channel	MAC Address
<input type="button" value="Save"/> <input type="button" value="Undo"/> <input type="button" value="Scan AP"/>		

Network ID (SSID): Network ID is used for identifying the Wireless LAN (WLAN). Client stations can roam freely over this product and other Access Points that have the same Network ID. (The factory setting is “default”)

SSID Broadcast: The router will Broadcast beacons that have some information, including ssid so that

The wireless clients can know how many ap devices by scanning function in the network. Therefore, This function is disabled, the wireless clients can not find the device from beacons.

Channel: The radio channel number. The permissible channels depend on the Regulatory Domain.


Security: Select the data privacy algorithm you want. Enabling the security can protect your data while it is transferred from one station to another.

Remote AP MAC : Choose “Manual” or scan one AP to copy to item1~4.

Universal Repeater Mode

Universal Repeater is a technology used to extend wireless coverage.

It provides the function to act as Adapter (client) and AP at the same time and can use this function to connect to a Root AP and use AP(SSID name is same with Root AP) function to service all wireless stations within its coverage. All the stations within the coverage of this access point can be bridged to the Root AP.



Universal Repeater Mode					
Item		Setting			
Wireless Radio		<input checked="" type="radio"/> Enable <input type="radio"/> Disable			
Wireless Operation Mode		Universal Repeater ▼			
Network ID(SSID)		<input type="text"/>			
Security		None ▼			
Select	SSID	Channel	Signal Strength	Security	MAC Address
<input type="button" value="Save"/> <input type="button" value="Undo"/> <input type="button" value="Scan AP"/>					

SSID (Wireless Network Name): Select "AP" or entry SSID manually to connect.

Security "There are several security types to use:

WEP :

When you enable the 128 or 64 bit WEP key security, please select one WEP key to be used and input 26 or 10 hexadecimal (0, 1, 2...8, 9, A, B...F) digits.

WPA2-PSK(AES)

1. Select Pre-share Key Mode

If you select HEX, you have to fill in 64 hexadecimal (0, 1, 2...8, 9, A, B...F) digits

If ASCII, the length of Pre-share key is from 8 to 63.

2. Fill in the key, Ex 12345678

WPA-PSK /WPA2-PSK

The router will detect automatically which Security type the client uses to encrypt.

1. Select Pre-share Key Mode

If you select HEX, you have to fill in 64 hexadecimal (0, 1, 2...8, 9, A, B...F) digits

If ASCII, the length of Pre-share key is from 8 to 63.

2. Fill in the key, Ex 12345678

Wireless Setting [HELP]	
Item	Setting
Wireless Radio	<input checked="" type="radio"/> On <input type="radio"/> Off
Wireless Off Schedule#	(00)Always <input type="radio"/> Enable <input checked="" type="radio"/> Disable
Network ID(SSID)	LevelOne
Wireless Mode	<input checked="" type="radio"/> Mixed mode <input type="radio"/> 11g only <input type="radio"/> 11b only <input type="radio"/> 11n only
SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Channel	6
WDS	Enter...
WPS	Enter...
Security	WPA-PSK / WPA2-PSK
Encryption	TKIP + AES
Preshare Key Mode	ASCII
Preshare Key	

Save Undo Wireless Client List...

Wireless Client List

Network ID (SSID): Network ID is used for identifying the Wireless LAN (WLAN). Client stations can roam freely over this product and other Access Points that have the same Network ID. (The factory setting is “default”)

SSID Broadcast: The router will Broadcast beacons that have some information, including ssid so that

The wireless clients can know how many ap devices by scanning function in the network. Therefore,

This function is disabled, the wireless clients can not find the device from beacons.

Channel: The radio channel number. The permissible channels depend on the Regulatory Domain.

WPS (WiFi Protection Setup)

WPS is WiFi Protection Setup which is similar to WCN-NET and offers safe and easy way in Wireless Connection.

ADMINISTRATOR's MAIN MENU		Status	Wizard	Advanced	Logout
BASIC SETTING		SECURITY SETTING	ADVANCED SETTING	TOOLBOX	
• Primary Setup	Wi-Fi Protected Setup				
• DHCP Server					
• Wireless					
• Change Password					
	Item	Setting			
	▶ WPS	<input checked="" type="radio"/> Enable <input type="radio"/> Disable			
	▶ Setup	<input checked="" type="radio"/> Current AP PIN <input type="radio"/> Configure Wireless Station			
	▶ Current PIN of the device	<input type="text" value="13938789"/> <input type="button" value="Generate New PIN"/>			
	▶ WPS state	Idle			
	Lock Wireless Security	<input checked="" type="checkbox"/> Enable			
	▶ WPS status	Configured <input type="button" value="Release"/>			
	<input type="button" value="Save"/> <input type="button" value="Trigger"/> <input type="button" value="Back"/>				

WDS(Wireless Distribution System)

WDS operation as defined by the IEEE802.11 standard has been made available. Using WDS it is possible to wirelessly connect Access Points, and in doing so extend a wired infrastructure to locations where cabling is not possible or inefficient to implement.

ADMINISTRATOR's MAIN MENU Status Wizard Advanced Logout

BASIC SETTING SECURITY SETTING ADVANCED SETTING TOOLBOX

Primary Setup
DHCP Server
Wireless
Change Password

It is a system that enables the interconnection of access points wirelessly.

WDS Setting [HELP]

Item	Setting	
▶ AP Mode:	AP Only ▼	
▶ Remote AP MAC MAC 1	<input type="text"/>	
MAC 2	<input type="text"/>	
MAC 3	<input type="text"/>	
MAC 4	<input type="text"/>	
Scanned AP's MAC: --- Select one --- ▼ Copy to Remote AP MAC: -- ▼		
SSID	Channel	MAC Address
Jay_189AS_test	1	00-50-18-00-0E-0B
Jay_189AS1_test	1	00-50-18-00-0E-0C
Jay_189AS2_test	1	00-50-18-00-0E-0D
aaron2	1	00-50-18-00-0E-FE
AP Storage	1	00-50-18-21-D1-2E

Security: Select the data privacy algorithm you want. Enabling the security can protect your data while it is transferred from one station to another.

There are several security types to use:

WEP :

When you enable the 128 or 64 bit WEP key security, please select one WEP key to be used and input 26 or 10 hexadecimal (0, 1, 2...8, 9, A, B...F) digits.

WPA-PSK

1. Select Encryption and Pre-share Key Mode

If you select HEX, you have to fill in 64 hexadecimal (0, 1, 2...8, 9, A, B...F) digits

If ASCII, the length of pre-share key is from 8 to 63.

2. Fill in the key, Ex 12345678

ADMINISTRATOR's MAIN MENU Status Wizard Advanced Logout

BASIC SETTING SECURITY SETTING ADVANCED SETTING TOOLBOX

- Primary Setup
- DHCP Server
- Wireless
- Change Password

Wireless Setting [HELP]	
Item	Setting
Wireless	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Network ID(SSID)	LevelOne
Wireless Mode	<input checked="" type="radio"/> Mixed mode <input type="radio"/> 11g only <input type="radio"/> 11b only
SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Channel	Auto
WDS	Enter...
WPS	Enter...
Security	WPA-PSK
Encryption	<input checked="" type="radio"/> TKIP <input type="radio"/> AES
Preshare Key Mode	ASCII
Preshare Key	

Save Undo Wireless Client List...

WPA2-PSK(AES)

1. Select Pre-share Key Mode

If you select HEX, you have to fill in 64 hexadecimal (0, 1, 2...8, 9, A, B...F) digits

If ASCII, the length of Pre-share key is from 8 to 63.

2. Fill in the key, Ex 12345678

WPA-PSK /WPA2-PSK

The router will detect automatically which Security type the client uses to encrypt.

1. Select Pre-share Key Mode

If you select HEX, you have to fill in 64 hexadecimal (0, 1, 2...8, 9, A, B...F) digits

If ASCII, the length of Pre-share key is from 8 to 63.

2. Fill in the key, Ex 12345678

ADMINISTRATOR's MAIN MENU Status Wizard Advanced Logout

BASIC SETTING SECURITY SETTING ADVANCED SETTING TOOLBOX

- Primary Setup
- DHCP Server
- Wireless
- Change Password

Wireless Setting [HELP]

Item	Setting
Wireless	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Network ID(SSID)	<input type="text" value="LevelOne"/>
Wireless Mode	<input checked="" type="radio"/> Mixed mode <input type="radio"/> 11g only <input type="radio"/> 11b only
SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Channel	<input type="text" value="Auto"/>
WDS	<input type="text" value="Enter..."/>
WPS	<input type="text" value="Enter..."/>
Security	<input type="text" value="WPA-PSK / WPA2-PSK"/>
Encryption	TKIP + AES
Preshare Key Mode	<input type="text" value="ASCII"/>
Preshare Key	<input type="text"/>

Wireless Client List

ADMINISTRATOR's MAIN MENU Status Wizard Advanced Logout

BASIC SETTING SECURITY SETTING ADVANCED SETTING TOOLBOX


- Primary Setup
- DHCP Server
- Wireless
- Change Password

Wireless Client List

Connected Time	MAC Address
Tue Jan 26 09:39:58 2010	00-1C-BF-00-C6-37

Universal Repeater Mode

If set to Adapter Mode (Client mode), this device can work like a wireless station when it's connected to a computer so that the computer can send packets from wired end to wireless interface.



Item		Setting			
Wireless Radio		<input checked="" type="radio"/> Enable <input type="radio"/> Disable			
Wireless Operation Mode		Client Mode <input type="button" value="v"/>			
SSID (Wireless Network Name)		<input type="text"/> <input type="button" value="Manual"/>			
Security		None <input type="button" value="v"/>			
Select	SSID	Channel	Signal Strength	Security	MAC Address
<input type="radio"/>	ssid243	1	100	None	90-94-E4-E5-9C-72
<input type="radio"/>	ssid244	1	100	None	90-94-E4-E5-9C-73

3.3.1.4 Change Password

ADMINISTRATOR's MAIN MENU
Status Wizard Advanced Logout

BASIC SETTING
SECURITY SETTING ADVANCED SETTING TOOLBOX


- Primary Setup
- DHCP Server
- Wireless
- Change Password

Change Password

Item	Setting
Old Password	<input type="password" value="....."/>
New Password	<input type="password"/>
Reconfirm	<input type="password"/>

You can change Password here. We **strongly** recommend you to change the system password for security reason.

3.3.3 Security Settings



3.3.3.4 MAC control

Administrator MAC Control

Regardless the MAC access configuration of administrator, specific MAC can access the device.

Administrator MAC Control
[HELP]

DHCP clients ID

ID	MAC Address	Enable
1	<input type="text" value="00-1D-72-12-A8-7F"/>	<input checked="" type="checkbox"/>
2	<input type="text"/>	<input type="checkbox"/>
3	<input type="text"/>	<input type="checkbox"/>

No change!

Internet Access Control

Item	Setting
▶ Access Control Type	MAC Access Control

Item	Setting
▶ Old Password	•••••
▶ New Password	
▶ Reconfirm	

MAC Address Control allows you to assign different access right for different users and to assign a specific IP address to a certain MAC address.

MAC Address Control Check "Enable" to enable the "MAC Address Control". All of the settings in this page will take effect only when "Enable" is checked.

Connection control Check "Connection control" to enable the controlling of which wired and wireless clients can connect to this device. If a client is denied to connect to this device, it means the client can't access to the Internet either. Choose "allow" or "deny" to allow or deny the clients, whose MAC addresses are not in the "Control table" (please see below), to connect to this device.

Association control Check "Association control" to enable the controlling of which wireless client can associate to the wireless LAN. If a client is denied to associate to the wireless LAN, it means the client can't send or receive any data via this device. Choose "allow" or "deny" to allow or deny the clients, whose MAC addresses are not in the "Control table", to associate to the wireless LAN.

Control table

ID	MAC Address	IP Address	C	A
1	<input type="text"/>	192.168.12. <input type="text"/>	<input type="checkbox"/>	<input type="checkbox"/>
2	<input type="text"/>	192.168.12. <input type="text"/>	<input type="checkbox"/>	<input type="checkbox"/>
3	<input type="text"/>	192.168.12. <input type="text"/>	<input type="checkbox"/>	<input type="checkbox"/>
4	<input type="text"/>	192.168.12. <input type="text"/>	<input type="checkbox"/>	<input type="checkbox"/>

"Control table" is the table at the bottom of the "MAC Address Control" page. Each row of this table indicates the MAC address and the expected IP address mapping of a client. There are four columns in this table:


MAC Address	MAC address indicates a specific client.
IP Address	Expected IP address of the corresponding client. Keep it empty if you don't care its IP address.
C	When " Connection control " is checked, check " C " will allow the corresponding client to connect to this device.
A	When " Association control " is checked, check " A " will allow the corresponding client to associate to the wireless LAN.

In this page, we provide the following Combobox and button to help you to input the MAC address.

You can select a specific client in the "DHCP clients" Combobox, and then click on the "Copy to" button to copy the MAC address of the client you select to the ID selected in the "ID" Combobox.

Previous page and Next Page To make this setup page simple and clear, we have divided the "Control table" into several pages. You can use these buttons to navigate to different pages.

Example:




In this scenario, there are three clients listed in the Control Table. Clients 1 and 2 are wireless, and client 3 is wired.

- 1.The "MAC Address Control" function is enabled.
- 2."Connection control" is enabled, and all of the wired and wireless clients not listed in the "Control table" are "allowed" to connect to this device.
- 3."Association control" is enabled, and all of the wireless clients not listed in the "Control table" are "denied" to associate to the wireless LAN.
- 4.Clients 1 and 3 have fixed IP addresses either from the DHCP server of this device or manually assigned:
 ID 1 - "00-12-34-56-78-90" --> 192.168.12.100
 ID 3 - "00-98-76-54-32-10" --> 192.168.12.101
 Client 2 will obtain its IP address from the IP Address pool specified in the "DHCP Server" page or can use a manually assigned static IP address.
 If, for example, client 3 tries to use an IP address different from the address listed in the Control table (192.168.12.101), it will be denied to connect to this device.

5. Clients 2 and 3 and other wired clients with a MAC address unspecified in the Control table are all allowed to connect to this device. But client 1 is denied to connect to this device.
6. Clients 1 and 2 are allowed to associate to the wireless LAN, but a wireless client with a MAC address not specified in the Control table is denied to associate to the wireless LAN. Client 3 is a wired client and so is not affected by Association control.

3.3.3.5 Miscellaneous Items



Administrator Time-out

The time of no activity to logout automatically. Set it to zero to disable this feature.

3.3.4 Advanced Settings

The screenshot shows the 'Advanced Setting' configuration page. The interface includes a top navigation bar with 'ADMINISTRATOR's MAIN MENU', 'Status', 'Wizard', 'Advanced', and 'Logout'. Below this is a secondary navigation bar with 'BASIC SETTING', 'SECURITY SETTING', 'ADVANCED SETTING', and 'TOOLBOX'. The left sidebar contains a tree view with 'System Time', 'System Log', and 'SNMP'. The main content area displays the following settings:

- System Time**
 - Allow you to set device time manually or consult network time.
- System Log**
 - Send system log to a dedicated host to specific recipients.
- SNMP**
 - Gives a user the capability to remotely manage a computer network by polling and setting terminal values and monitoring network events.

3.3.4.1 System Time

The screenshot shows the 'System Time' configuration page. The interface includes a top navigation bar with 'ADMINISTRATOR's MAIN MENU', 'Status', 'Wizard', 'Advanced', and 'Logout'. Below this is a secondary navigation bar with 'BASIC SETTING', 'SECURITY SETTING', 'ADVANCED SETTING', and 'TOOLBOX'. The left sidebar contains a tree view with 'System Time', 'System Log', and 'SNMP'. The main content area displays the following settings:

Item	Setting
System Time	2009年6月1日 上午 12:16:37
<input type="radio"/> Set Date and Time using PC's Date and Time	
PC Date and Time	2013年1月14日 下午 07:25:22
<input checked="" type="radio"/> Set Date and Time manually	
Date	Year: 2009 Month: Jun Day: 01
Time	Hour: 0 (0-23) Minute: 0 (0-59) Second: 0 (0-59)

Buttons: Save, Undo

Get Date and Time


Set Date and Time manually

Selected if you want to Set Date and Time manually.

Set Date and Time manually

Selected if you want to Set Date and Time manually.

3.3.4.2 System Log



This page support two methods to export system logs to specific destination by means of syslog(UDP) and SMTP(TCP). The items you have to setup including:

IP Address for Syslog

Host IP of destination where syslogs will be sent to.

Check **Enable** to enable this function.

E-mail Alert Enable

Check if you want to enable Email alert (send syslog via email).

SMTP Server IP and Port

Input the SMTP server IP and port, which are concated with ':'. If you do not specify port number, the default value is 25.

For example, "mail.your_url.com" or "192.168.1.100:26".

Send E-mail alert to

The recipients who will receive these logs. You can assign more than 1 recipient, using ';' or ',' to separate these email addresses.

3.3.4.4 SNMP

Item	Setting
▶ Enable SNMP	<input checked="" type="checkbox"/> Local
▶ Get Community	public
▶ Set Community	private
▶ IP 1	
▶ IP 2	
▶ IP 3	
▶ IP 4	
▶ SNMP Version	<input type="radio"/> V1 <input checked="" type="radio"/> V2c

Save Undo

In brief, SNMP, the Simple Network Management Protocol, is a protocol designed to give a user the capability to remotely manage a computer network by polling and setting terminal values and monitoring network events.

Enable SNMP

You must check Local, Remote or both to enable SNMP function. If Local is checked, this device will response request from LAN. **Get Community**

Setting the community of GetRequest your device will response.

Set Community

Setting the community of SetRequest your device will accept.


IP 1, IP 2, IP 3, IP 4

Input your SNMP Management PC's IP here. User has to configure to where this device should send SNMP Trap message.


SNMP Version

Please select proper SNMP Version that your SNMP Management software supports.

3.3.5 Toolbox




3.3.5.1 View Log




You can View system log by clicking the **View Log** button

3.3.5.2 Firmware Upgrade



You can upgrade firmware by clicking **Firmware Upgrade** button.

3.3.5.3 Backup Setting



You can backup your settings by clicking the **Backup Setting** button and save it as a bin file. Once you want to restore these settings, please click **Firmware Upgrade** button and use the bin file you saved.

3.3.5.4 Reset to default



You can also reset this product to factory default by clicking the **Reset to default** button.

3.3.5.5 Reboot



You can also reboot this product by clicking the **Reboot** button.

Appendix A FAQ and Troubleshooting

What can I do when I have some trouble at the first time?

1. Why can I not connect the router even if the cable is plugged in Lan port and the led is light?

A: First, please check Status Led. If the device is normal, the led will blink per second.

If not, please check How blinking Status led shows.

There are many abnormal symptoms as below:

Status Led is bright or dark in work: The system hanged up .Suggest powering off and on the router. But this symptom often occurs, please reset to default or upgrade latest fw to try again.

Status led flashes irregularly: Maybe the root cause is Flash rom and please press reset Button to reset to default or try to use Recovery mode.(Refer to Q3 and Q4)

Status flashes very fast while powering on: Maybe the router is the recovery mode and please refer to Q4.

2. How to reset to factory default?

A: Press Wireless on /off and WPS button simultaneously about 5 sec

Status will start flashing about 5 times, remove the finger. The RESTORE process is completed.

How do I connect router by using wireless?

1.How to start to use wireless?

A: First, make sure that you already installed wireless client device in your computer. Then check the Configuration of wireless router. The default is as below:


Item	Setting
Wireless	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Network ID(SSID)	default
Wireless Mode	<input type="radio"/> 11 b/g/n Mixed <input type="radio"/> 11n only
SSID Broadcast	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Channel	11
Security	None

[Save](#) [Undo](#) [WDS Setting...](#)
[MAC Address Control...](#) [Wireless Client List...](#)


About wireless client, you will see wireless icon:




Then click and will see the ap list that wireless client can be accessed:



If the client can not access your wireless router, please refresh network list again. However, I still can not fine the device which ssid is "default", please refer to Q3.



Choose the one that you will want to connect and Connect:



If successfully, the computer will show



and get ip from router:




2. When I use AES encryption of WPA-PSK to connect even if I input the correct pre-share key?

A: First, you must check if the driver of wireless client supports AES encryption. Please refer to the below:



If SSID is default and click "Properties" to check if the driver of wireless client supports AES encryption.



3. When I use wireless to connect the router, but I find the signal is very low even if I am close to the router?

A: Please check if the wireless client is normal, first. If yes, please send the unit to the seller and verify what the problem is.