# TEW-453APB

Hot Spot Wireless Access Point Quick Installation Guide

Point d'accès sans fil sensible Guide d'installation rapide

Drahtloser Access Point für Hotspots Kurzanleitung zur Installation

Guía de instalación rápida del punto de acceso inalámbrico Hot Spot

Version 03.02.2005





## **Table of Contents**

English	1
Prepare for Installation Install Hardware	2
Configure TCP/IP Settings Configure the Access Point	
Troubleshooting	11

## **English QIG**

## 1. Prepare for Installation

Thank you for purchasing TRENDnet's TEW-453APB Hot Spot Wireless Access Point.

This guide will help you set-up your Access Point quickly and easily. Just follow the step-by-step instructions below, and enjoy the benefits of accessing the Internet without ever being tied down to wires! If you run into problems, please refer to the Troubleshooting section. If you need further technical support, please visit www.TRENDNET.com or call technical support by phone.

### **Verify Package Contents**

Please make sure you have everything in the box:



## **Verify Equipment**

Before setting up the Access Point, you should have the following:

- 1. A computer with Wired (RJ45) or Wireless network card.
- 2. TCP/IP protocol installed on the Computer.
- 3. A web browser such as Internet Explorer (5.0 or higher) or Netscape Navigator (4.7 or higher).
- **4.** A Hub or Switch connecting your existing wired network.
- An RJ-45 Network Cable for connecting the Access Point to your network switch.

1

**English** 

### 2. Install Hardware

- **1.** Locate an optimum location for the Access Point. The best place for the Access Point is usually at the center of your wireless network.
- Connect the RJ45 network cable to the Access Point, then connect the other end of the network cable to a Switch or Hub. The Access Point is now connected to your 10/100mbps network.
- Connect the power adapter to the Access Point. Make sure you use the power adapter supplied with the Access Point; using a different power adapter may damage the unit.



**NOTE:** If you are using a wired computer to configure the Access Point, please connect this computer to the same Switch or Hub the TEW-453APB is connected to.



## **Verify Hardware Installation**


Make sure the front panel lights are on: Power, LAN, Wireless.

## 3. Configure TCP/IP Settings


Before the Access Point can be accessed and configured, the computer's TCP/IP settings need to be changed.

#### Windows 98SE/ME


- 1. Find the **Start** button located on the Desktop.
- 2. Click Start, click Settings, and then click on Control Panel.
- Double-Click the Network Icon, and the Network Properties box will appear.
- 4. Under the Configuration tab, locate and select TCP/IP with the corresponding network card. Then click on the Properties button and the TCP/IP Properties window will appear.



 Under the IP Address tab, click on Specify an IP address and enter 192.168.0.50 for IP address and 255.255.255.0 for Subnet Mask and click OK.



6. Click OK.



- 7. At this point, the installation may require files from your Windows CD-ROM. If you are prompted for the location of these files, insert Windows 98 CD-ROM into your CD-ROM drive and select CD-ROM drive.
- **8.** After the files load, the System Settings Change message appears, click **Yes** to reboot your system.




**<u>NOTE:</u>** If this message does not appear, restart your computer manually.

9. Your computer is now ready to access and configure the Access Point.

#### Windows 2000/XP


- 1. Find the **Start** button located on the Desktop.
- 2. Click Start, and click on Control Panel. For Windows 2000, click Start, highlight Settings, and click Control Panel.
- 3. Double-Click the **Network Connection** Icon.
- Right-Click on the Local Area Connection icon and then click on Properties. The Local Area Connection Properties box will appear.




5. Under the **General** tab, locate and click **Internet Protocol TCP/IP** and then click **Properties**. The Internet Protocol (TCP/IP) Properties box will appear.



 Click on Use the following IP address. Enter 192.168.0.50 for IP address and 255.255.255.0 for Subnet Mask, and click OK.



#### 7. Click OK.



8. Your computer is ready to access and configure the Access Point.

## 4. Configure the Access Point

## From a Wired Computer


 Open a web browser (Internet Explorer or Netscape) and enter http://192.168.0.228 in the address bar, then press the Enter key. The TEW-453APB's authentication window will appear. Type admin for User name, and type password for Password.



#### 2. Click System.



Select your country from the pull down menu, click Fixed IP Address, and type in your IP address, Subnet Mask, Gateway, and DNS to match your current network settings. Click Save.



4. Click OK.



5. Click Apply/Restart.



6. The TEW-453APB is now ready for your Wireless Network.

## **Troubleshooting**

Q1: I specified the IP address http://192.168.0.228 in my Internet browser's address bar, but an error message says "The page cannot be displayed". How can I get into the TEW-453APB's web configuration page?

A1: Please make sure that your workstation and the TEW-453APB are in the same network segment. Make sure you change your workstation's IP Address to 192.168.0.X where "X" is a number from 1 to 227 and 229 to 254. If your workstation and the TEW-453APB lie in the same network segment, then double-check the connection between the TEW-453APB and your switch, and make sure that the power adapters for your switch and the TEW-453APB are plugged in.

Q2: After I successfully configured the Access Point to meet my network settings, I cannot connect to my network using wireless computers.

A2: If you have a DHCP server in your network, you need to go into TCP/IP settings again and re-select "Obtain an IP automatically" for Windows 98/ME and "Obtain an IP Address automatically" for Windows 2000/XP to allow the PC to regain an IP address from your DHCP server.

Q3. When I configure the network settings for the TEW-453APB, I don't have a Domain Name Server, but the TEW-453APB requires a DNS entry. What do I do?

A3: In this case, your DNS entry is the same as your Gateway's entry. So if your Gateway is 192.168.1.1, then your DNS is 192.168.1.1.

Q4. All the settings are set correctly, but I still can't use the Access Point, what should I do?

**A4:** You can find additional information in the User's Guide. If you still have problems, contact our Technical Support by email or phone.

This equipment has been tested and found to comply with FCC and CE Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received including interference that may cause undesired operation.





## **Product Warranty Registration**

Please take a moment to register your product online. Go to TRENDware's website at http://www.TRENDNET.com

## TRENDnet Technical Support

#### US/Canada Support Center

#### **European Support Center**

#### Contact

**Telephone:** 1(310) 626-6252 **Fax:** 1(310) 626-6267 **Email:** support@trendnet.com

#### **Tech Support Hours**

7:30am - 6:00pm Pacific Standard Time Monday - Friday

#### Contact

#### Telephone

Deutsch: +49 (0) 6331 / 268-460 Français: +49 (0) 6331 / 268-461 Español: +49 (0) 6331 / 268-462 English: +49 (0) 6331 / 268-463 Italiano: +49 (0) 6331 / 268-464 Dutch: +49 (0) 6331 / 268-465 Fax: +49 (0) 6331 / 268-466

#### **Tech Support Hours**

8:00am - 6:00pm Middle European Time Monday - Friday

#### TRENDware International, Inc.

3135 Kashiwa Street. Torrance, CA 90505

http://www.TRENDNET.com